

Sometimes you need a lot of equipment.

Sometimes you don't.

## Lexmark X5470 Business Edition

# All-In-One with Fax and Photo Features

Print fast! Up to 25 ppm black and 18 ppm colour\*

#### • Full featured fax with convenient auto document feeder

- Direct photo printing from memory cards or with PictBridge
- Scan-back proof sheet option allows for PC-free photo printing
- 1-Touch PC-free copy

## Business club

- print up to 1.000 pages with the 2 high yield black cartridges (in the box)
- benefit from 3 years of warranty coverage as members of the Club

Find registration details at www.lexmark.xx/businessclub



## Lexmark X5470 Business Edition

#### **FEATURES**

Print		
Resolution: Mode (dpi)	Glossy paper	Plain Paper
Best	4800 x 1200	1200 x 1200
Ink drop size:	Black 24 pL Colour 4/10 pL Photo 5/9 pL	
Acoustics:	50 dBa (operating)	
Duty cycle:	3000 p/month	
Print Technology:	Thermal Inkjet: 4 colour Yellow, Black, 6 colour Cyan & Light Magenta	
<ul> <li>Print Speed Mode</li> </ul>	Black	Colour
Quick (ppm)	Up to 25	Up to 18
• Acoustics:	40 dBA (operating)	
Resolution:	600 x 2400 dpi (optical)	)
Colour depth:	48 bits internal True Co 24 bits external True Co	
• Scan area:	216 mm x 355 mm	
Scan Technology:	CIS	
• Acoustics:	50 dBa (operating)	
PC free copy		
• Up to 99 copies at o	one time	
Reduce/Enlarge:	25% to 400%	

Speed

Mode	Black	Colour
Quick (ppm)	Up to 17	Up to 11

Fax

- Standalone Fax
- Send / Receive legal, letter & A4
- 33.6 Kbps speed
- 10 page Auto Document Feeder (ADF)
- 89 speed dials
- Caller ID (where available)
- Automatic Redial / Busy Redial



### TECHNOLOGY

## 

		DUOTO	
BLACK CARTRIDGE     No. 32: up to 200 pages at	OLOUR CARTRIDGE     No. 33 (in the box): up		<u>) CARTRIDGE</u> 31: up to 135 10 x 1
5% coverage • No. 34 (2 in the box) : up to 475 pages at 5% coverage	190 pages** at 15% c • No. 35: up to 450 pag coverage		DS
Miscellaneous • Memory Card Compatibility: CompactFlash I and II, Smarth Memory Stick- Memory Stick I Duo Pro with adapter), Secure Card, MultiMediaCard (MMC), readers, RS-MMC (with adapter, xD Card, Mini Secure Digital (M with adapter, SanDisk Transflat Module (with adapter)	Aedia ard, Sony       • 32 M         Pro (Duo and       • Powe         Digital (SD)       Volta;         4 built-in card       • Borda;         n), Microdrive,       • USB		erial Flash 10 - 240 VAC Input
Minimum system requirements     Operating system	: Processor Speed (MI		Hard disc space (MB)
Windows 2000/XP Windows 64/Vista Mac OS X 10.3.X – 10.4.X (Pc	Pentium II 800 or Hig wer PC) G3 500		500 800 500

- Machine retracted:
- Machine extended:
- Machine weight:
- Packaged weight:
- Packaged weight:
- Width 454 mm, Depth 320 mm, Height 192 mm Width 455 mm, Depth 521 mm, Height 297 mm 6.5 kg
- 7.8 kg Width 567 mm, Depth 398 mm, Height 263 mm

\* Printing in draft mode and excluding time to first page feed. \*\* Estimated yield based on page coverage 5% cyan, 5% magenta, 5% yellow. Based on average results obtained during plain paper, normal mode printing. Actual page yield may vary. Contact Lexmark for more details. \*\*\* Estimated yield based colour balanced 10 x 15 photo. Based on average results obtained during glossy paper, photo mode printing. Actual yield may vary. Contact Lexmark for more details.

Lexmark, PrecisionPhoto, PrecisionSense, Color Jetprinter, ColorFine and evercolor are trademarks of Lexmark International, Inc. Mac and iMac are trademarks of Apple Computer, Inc., registered in the United States and other countries. Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective holders. All product specifications or features are subject to change without notice

75% of the top banks, retailers and pharmacies use Lexmark

